
Redox ladder – electron donors and acceptors



Impact of thermal on redox

Steam injection:

Air: Reduce risk of NAPL condensation

Air: Enhance removal in vapor phase

Air/O₂: Stimulate degradation reactions

ERH:

Boiling under vacuum – removes dissolved gases such as O₂

Hydrogen formation around electrodes possible


Reactions around Fe(0) used for electrodes

ISTD-TCH:

Boiling under vacuum – removes dissolved gases such as O₂

Air can be added for in-situ destruction

Environment diagram



Abbreviations


T Temperature

COC Contaminant concentration

Sat Water saturation

NPK Nutrient availability


Eh Oxidation-reduction potential



Conclusions


Redox chemistry is key for reactions


Geochemical changes can be significant during thermal





Bioremediation may

- be discouraged due to quick changes in environmental conditions (T, E_h)
- be encouraged by stimulation and augmentation with little competition










Abbreviations


TEFPR – thermally enhanced free product recovery



Abbreviations

TEFPR – thermally enhanced free product recovery


TEX – thermally enhanced X



Abbreviations

TEFPR – thermally enhanced free product recovery


TEX – thermally enhanced X




Abbreviations

TEFPR – thermally enhanced free product recovery

TEX – thermally enhanced X



Treatment cost



Combo not universally applicable
Relatively high unit treatment cost
Most relevant when remedial goals
are very stringent and
concentrations high

Conclusions

- It is not simple
- Heating above 40°C favors new microorganisms
- May be beneficial to augment after cool-down
- Geochemistry rules what happens
- Starting and target concentrations are essential
- Case by case evaluation simple answers are dangerous
- Cost varies dramatically from site to site (so does the most economic technology)